

Specifications

MODEL	MP-15	MP-25	MP-38	MP-55	MP-75	MP-90	MP-115	MP-125	MP-200	MP-300	MP-450	MP-600	MP-800	MP-1000	
Capacity (Litres)	15	25	38	55	75	90	115	125	200	300	450	600	800	1000	
Dimension (mm)	305 x 405	305 x 610	355 x 640	430 x 600	430 x 780	430 x 900	510 x 960	510 x 1000	510 x 1610	560 x 1550	790 x 1125	790 x 1500	965 x 1355	965 x 1670	
Rating (kW) [Voltage (Volt)]	3/240v/1ph [240]					9/415v/3ph [415]		3/240v/1ph [240]	3/240v/1ph [240]	3/240v/1ph [240]	3/240v/1ph [240]	3/240v/1ph [240]	3/240v/1ph [240]	3/240v/1ph [240]	9/415v/3ph [415]
Thermostat	60° C														
Thermal Cut-Out	93° C Manual Reset - 1 Phase / 82° C Manual Reset - 3 Phase														
Inner Tank Material	Special High Gauge Stainless Steel														
Nominal Working Pressure	100 p.s.i.														
Test Pressure	150 p.s.i.														
Recommend Inlet Pressure	60 p.s.i. (maximum)														
Cold Expansion Valve Setting	145 p.s.i.														
P.T. Valve Setting	125 p.s.i. / 99° C														
Insulation Material	CFC-Free Polyurethane Foam														
Casing	Zinc / Aluminium Alloy														
Inner Tank Warranty	5 Years														
Electrical Parts Warranty	1 Year														

Rating (kW) : (Other options) 12/18/27kW available on request